

CX330 Excavator



ENGINE

Model Case 6TAA-830
Type 4-stroke, turbocharged
Cylinders 6
Bore/Stroke 4.49" x 5.31"
(114 x 135 mm)
Displacement 505 in³ (8270 cc)
Fuel injection Direct
Fuel injection pump Electronic
Fuel Diesel
Cooling Liquid
Horsepower per SAE J1349
Gross... 275 hp (205 kW) @ 2000 rpm
Net 259 (193 kW) @ 2000 rpm
Maximum torque @ 1400 rpm
Net 793 lb-ft (1075 N·m)

BOOM/ARM

Boom

Length 21'2" (6.45 m)
Boom w/arm cylinder
& plumbing 6,982 lb (3167 kg)
Hoist cylinders (2) 761 lb (345 kg) ea
Total weight 8,503 lb (3857 kg)

13'3" Arm (4.04 m)

Length 13'3" (4.04 m)
Bare arm 3,150 lb (1429 kg)
Bucket cylinder linkage
& plumbing 1,356 lb (615 kg)
Total weight 4,506 lb (2044 kg)

10'8" Arm (3.25 m)

Length 10'8" (3.25 m)
Bare arm 2,414 lb (1095 kg)
Bucket cylinder linkage
& plumbing 1,356 lb (615 kg)
Total weight 3,770 lb (1710 kg)

8'8" Arm (2.63 m)

Length 8'8" (2.63 m)
Bare arm 2,275 lb (1032 kg)
Bucket cylinder linkage
& plumbing 1,356 lb (615 kg)
Total weight 3,631 lb (1647 kg)

UNDERCARRIAGE

Number of rollers
Top, each track 2
Bottom, each track 8
Number of shoes
Triple grouser – each side 48
Link pitch 8.5" (215.9 mm)

HYDRAULICS

Pumps (2) Variable displacement
axial piston design

Capacity –
Maximum 2 x 75 gpm
(284 L/min)

System relief pressure –
Standard 4975 psi (34.3 MPa)
Power Boost 5410 psi (37.3 MPa)

Control valves –
4-spool section for left track travel,
boom, bucket and arm
5-spool section for right track
travel, boom, auxiliary, swing
and arm
Boom and arm anti-drift valves

Pilot control hydraulic system –
Pump (1) Gear design
Maximum capacity 8.1 gpm
(30.5 L/min)
Relief pressure 566 psi (3.9 MPa)

Swing –
Motor (1) Fixed displacement
axial piston design
Speed 0-9.6 rpm
Brake Spring-applied
hydraulically released with
dual cushion relief
Tail swing radius 11'4" (3.45 m)

Travel –
Motor (1) Two-speed
axial piston design
Final drive Planetary gear
reduction
Drawbar pull 60,923 lb (271 kN)

Travel Speeds –
Auto shift high to low
Forward/Reverse
Low 2.0 mph (3.2 km/h)
High 3.4 mph (5.5 km/h)

Travel control valve –
Dual stage relief and counter-
balance design

HYDRAULIC CYLINDERS

Boom cylinders (2) –
Bore diameter 5.7" (145 mm)
Rod diameter 3.9" (100 mm)
Stroke 58.9" (1495 mm)
Arm cylinder (1) –
Bore diameter 6.7" (170 mm)
Rod diameter 4.7" (120 mm)
Stroke 68.8" (1748 mm)
Bucket cylinder (1) –
Bore diameter 5.9" (150 mm)
Rod diameter 4.1" (105 mm)
Stroke 47.6" (1210 mm)

ELECTRICAL

Voltage 24 volts,
negative ground
Alternator 50 amp
Batteries (2) Low-maintenance
140 Ah (5 hr rate)

SERVICE CAPACITIES

Hydraulic tank
Refill capacity 46 gal (175 L)
Total system 92 gal (350 L)
Final drive (per side) ... 11.6 qt (11 L)
Swing drive 6.3 qt (6.0 L)
Engine
w/filter change 22.2 qt (21 L)
Fuel 153 gal (580 L)
Radiator 46.5 qt (44 L)

OPERATING WEIGHT

With 10'8" (3.25 m) arm, 31.5"
(800 mm) track shoes, 2,544 lb
(1156 kg) bucket, 165 lb (75 kg)
operator, full fuel and standard
equipment 78,043 lb (35 400 kg)

LIFT CAPACITIES

13'3" (4.04 m) Arm Lift capacities calculated using a 2,544 lb (1154 kg) bucket, 16,314 lb (7400 kg) counterweight operating in "Light" Mode

Load (Lift Point) Height	10' (3.05 m)		15' (4.57 m)		20' (6.1 m)		25' (7.62 m)		30' (9.14 m)		MAXIMUM REACH			
	END	SIDE	END	SIDE	END	SIDE	END	SIDE	END	SIDE	@	END	SIDE	
+25' (7.62 m)												27'7" (8.4 m)	10,330 lbs* (4685 kg)	10,330 lbs* (4685 kg)
+20' (6.1 m)										10,943 lbs* (4964 kg)	10,704 lbs (4855 kg)	31'6" (9.6 m)	7,566 lbs* (3432 kg)	7,566 lbs* (3432 kg)
+15' (4.57 m)										15,591 lbs* (7072 kg)	14,517 lbs (6585 kg)	33'2" (10.1 m)	7,670 lbs* (3479 kg)	7,670 lbs* (3479 kg)
+10' (3.05 m)			26,749 lbs* (12 133 kg)	26,749 lbs* (12 133 kg)	20,758 lbs* (9416 kg)	19,785 lbs (8974 kg)	17,578 lbs* (7973 kg)	13,686 lbs (6208 kg)	15,680 lbs* (7112 kg)	9,927 lbs (4503 kg)		34'1" (10.38 m)	8,039 lbs* (3646 kg)	7,766 lbs (3522 kg)
+5' (1.52 m)	28,307 lbs* (12 840 kg)	28,307 lbs* (12 840 kg)	33,756 lbs* (15 311 kg)	28,407 lbs (12 885 kg)	24,437 lbs* (11 084 kg)	18,261 lbs (8283 kg)	19,655 lbs* (8915 kg)	12,838 lbs (5823 kg)	15,495 lbs (7028 kg)	9,445 lbs (4284 kg)		34'2" (10.4 m)	8,711 lbs* (3951 kg)	7,451 lbs (3380 kg)
Ground-line	25,954 lbs* (11 772 kg)	25,954 lbs* (11 772 kg)	38,250 lbs* (17 350 kg)	26,377 lbs (11 964 kg)	27,263 lbs* (12 366 kg)	17,074 lbs (7745 kg)	20,121 lbs (9127 kg)	12,130 lbs (5502 kg)	15,049 lbs (6826 kg)	9,034 lbs (4098 kg)		33'6" (10.2 m)	9,800 lbs* (4445 kg)	7,476 lbs (3339 kg)
-5' (-1.52 m)	32,247 lbs* (14 627 kg)	32,247 lbs* (14 627 kg)	39,780 lbs* (18 044 kg)	25,425 lbs (11 532 kg)	27,976 lbs (12 690 kg)	16,359 lbs (7420 kg)	19,604 lbs (8892 kg)	11,663 lbs (5290 kg)	14,770 lbs (6699 kg)	8,777 lbs (3981 kg)		32'1" (9.8 m)	11,563 lbs* (5245 kg)	7,890 lbs (3579 kg)
-10' (-3.05 m)	41,964 lbs* (19 034 kg)	41,964 lbs* (19 034 kg)	38,724 lbs* (17 565 kg)	25,213 lbs (11 436 kg)	27,676 lbs (12 554 kg)	16,098 lbs (7302 kg)	19,412 lbs (8805 kg)	11,490 lbs (5212 kg)				29'9" (9.1 m)	14,634 lbs* (6638 kg)	8,867 lbs (4022 kg)
-15' (-4.57 m)	50,211 lbs* (22 775 kg)	50,211 lbs* (22 775 kg)	35,007 lbs* (15 879 kg)	25,557 lbs (11 592 kg)	25,992 lbs* (11 790 kg)	16,266 lbs (7378 kg)	19,555 lbs* (8870 kg)	11,684 lbs (5300 kg)				26'3" (7.9 m)	18,009 lbs* (8169 kg)	10,895 lbs (4942 kg)
-20' (6.1 m)	38,185 lbs* (17 320 kg)	38,185 lbs* (17 320 kg)	27,483 lbs* (12 466 kg)	26,502 lbs (12 021 kg)	19,849 lbs* (9003 kg)	16,988 lbs (7706 kg)						21'1" (6.4 m)	18,294 lbs* (8298 kg)	15,769 lbs (7153 kg)


10'8" (3.25 m) Arm Lift capacities calculated using a 2,544 lb (1154 kg) bucket, 16,314 lb (7400 kg) counterweight operating in "Light" Mode

Load (Lift Point) Height	10' (3.05 m)		15' (4.57 m)		20' (6.1 m)		25' (7.62 m)		30' (9.14 m)		MAXIMUM REACH			
	END	SIDE	END	SIDE	END	SIDE	END	SIDE	END	SIDE	@	END	SIDE	
+25' (7.62 m)												24'5" (7.4 m)	13,915 lbs* (6312 kg)	13,915 lbs* (6312 kg)
+20' (6.1 m)												28'10" (8.8 m)	10,052 lbs* (4559 kg)	10,052 lbs* (4559 kg)
+15' (4.57 m)					20,014 lbs* (9078 kg)	20,014 lbs* (9078 kg)	17,718 lbs* (8037 kg)	14,394 lbs (6529 kg)	12,737 lbs* (5777 kg)	10,390 lbs (4713 kg)		30'8" (9.3 m)	10,261 lbs* (4645 kg)	9,976 lbs (4525 kg)
+10' (3.05 m)	35,063 lbs* (15 904 kg)	35,063 lbs* (15 904 kg)	31,330 lbs* (14 211 kg)	30,474 lbs (13 823 kg)	23,489 lbs* (10 654 kg)	19,492 lbs (8841 kg)	19,532 lbs* (8859 kg)	13,671 lbs (6201 kg)	16,092 lbs* (7299 kg)	10,038 lbs (4553 kg)		31'7" (9.62 m)	10,851 lbs* (4922 kg)	9,150 lbs (4150 kg)
+5' (1.52 m)	17,050 lbs* (7734 kg)	17,050 lbs* (7734 kg)	37,415 lbs* (16 971 kg)	27,930 lbs (12 669 kg)	26,761 lbs* (12 138 kg)	18,203 lbs (8257 kg)	20,984 lbs (9518 kg)	12,962 lbs (5879 kg)	15,684 lbs (7114 kg)	9,662 lbs (4382 kg)		31'8" (9.65 m)	11,898 lbs* (5397 kg)	8,805 lbs (3994 kg)
Ground-line	24,087 lbs* (10 926 kg)	24,087 lbs* (10 926 kg)	40,353 lbs* (18 304 kg)	26,551 lbs (12 043 kg)	28,925 lbs (13 120 kg)	17,293 lbs (7844 kg)	20,373 lbs (9241 kg)	12,411 lbs (5629 kg)	15,367 lbs (6970 kg)	9,370 lbs (4250 kg)		31'0" (9.4 m)	13,617 lbs* (6176 kg)	8,900 lbs (4037 kg)
-5' (-1.52 m)	34,916 lbs* (15 838 kg)	34,916 lbs* (15 838 kg)	40,338 lbs* (18 297 kg)	26,074 lbs (11 827 kg)	28,436 lbs (12 898 kg)	16,832 lbs (7635 kg)	20,035 lbs (9088 kg)	12,106 lbs (5491 kg)				29'5" (8.9 m)	15,669 lbs (7107 kg)	9,514 lbs (4315 kg)
-10' (-3.05 m)	48,493 lbs* (21 996 kg)	48,493 lbs* (21 996 kg)	37,825 lbs* (17 157 kg)	26,170 lbs (11 870 kg)	28,205 lbs* (12 793 kg)	16,785 lbs (7613 kg)	20,038 lbs (9089 kg)	12,109 lbs (5492 kg)				26'11" (8.2 m)	18,019 lbs (8173 kg)	10,941 lbs (4963 kg)
-15' (-4.57 m)	44,393 lbs* (20 136 kg)	44,393 lbs* (20 136 kg)	32,369 lbs* (14 682 kg)	26,758 lbs (12 137 kg)	24,191 lbs* (10 973 kg)	17,175 lbs (7790 kg)						22'11" (7.0 m)	20,012 lbs* (9077 kg)	14,118 lbs (6404 kg)
-20' (6.1 m)			21,613 lbs* (9803 kg)	21,613 lbs* (9803 kg)								16'8" (5.1 m)	19,088 lbs* (8658 kg)	19,088 lbs* (8658 kg)

8'8" (2.63 m) Arm Lift capacities calculated using a 2,544 lb (1154 kg) bucket, 16,314 lb (7400 kg) counterweight operating in "Light" Mode

Load (Lift Point) Height	10' (3.05 m)		15' (4.57 m)		20' (6.1 m)		25' (7.62 m)		30' (9.14 m)		MAXIMUM REACH			
	END	SIDE	END	SIDE	END	SIDE	END	SIDE	END	SIDE	@	END	SIDE	
+20' (6.1 m)												27'0" (8.2 m)	14,722 lbs* (6678 kg)	12,765 lbs* (5790 kg)
+15' (4.57 m)					21,926 lbs* (9945 kg)	20,477 lbs (9288 kg)	19,121 lbs* (8673 kg)	14,218 lbs (6449 kg)				29'0" (8.8 m)	15,004 lbs* (6806 kg)	10,975 lbs (4978 kg)
+10' (3.05 m)			34,249 lbs* (15 535 kg)	29,418 lbs (13 344 kg)	25,145 lbs* (11 405 kg)	19,112 lbs (8669 kg)	20,707 lbs* (9392 kg)	13,535 lbs (6139 kg)				29'11" (9.1 m)	15,852 lbs* (7190 kg)	10,029 lbs (4549 kg)
+5' (1.52 m)			39,237 lbs* (17 797 kg)	27,188 lbs (12 332 kg)	27,960 lbs* (12 682 kg)	17,923 lbs (8130 kg)	20,891 lbs (9476 kg)	12,888 lbs (5846 kg)	15,717 lbs (7129 kg)	9,701 lbs (4400 kg)		30'1" (9.17 m)	15,655 lbs (7101 kg)	9,662 lbs (4382 kg)
Ground-line			40,716 lbs* (18 468 kg)	26,240 lbs (11 902 kg)	28,808 lbs* (13 067 kg)	17,168 lbs (7787 kg)	20,380 lbs (9244 kg)	12,428 lbs (5637 kg)				29'4" (8.9 m)	16,018 lbs (7266 kg)	9,819 lbs (4454 kg)
-5' (-1.52 m)	36,164 lbs* (16 404 kg)	36,164 lbs* (16 404 kg)	39,480 lbs* (17 908 kg)	26,076 lbs (11 828 kg)	28,472 lbs (12 915 kg)	16,876 lbs (7655 kg)	20,176 lbs (9152 kg)	12,244 lbs (5554 kg)				27'8" (8.4 m)	17,377 lbs (7882 kg)	10,616 lbs (4815 kg)
-10' (-3.05 m)	48,416 lbs* (21 961 kg)	48,416 lbs* (21 961 kg)	35,859 lbs* (16 265 kg)	26,408 lbs (11 978 kg)	27,142 lbs* (12 311 kg)	17,010 lbs (7715 kg)						24'11" (7.6 m)	20,462 lbs (9281 kg)	12,480 lbs (5661 kg)
-15' (-4.57 m)	37,846 lbs* (17 167 kg)	37,846 lbs* (17 167 kg)	28,901 lbs* (13 109 kg)	27,265 lbs (12 367 kg)	21,330 lbs* (9675 kg)	17,690 lbs (8024 kg)						20'8" (6.3 m)	20,311 lbs* (9213 kg)	16,939 lbs (7683 kg)


*Lift capacities do not exceed 75% of the minimum tipping load or 87% of the hydraulic lift capacity. Capacities that are marked with an asterisk are hydraulic limited.



DIMENSIONS

	13'3" (4.04 m) Arm	10'8" (3.25 m) Arm	8'8" (2.63 m) Arm
A. Overall height	11'6" (3.51 m)	10'10" (3.29 m)	11'7" (3.53 m)
B. Cab height	10'1" (3.07 m)	10'1" (3.07 m)	10'1" (3.07 m)
C. Overall length	36'5" (11.09 m)	36'3" (11.05 m)	36'6" (11.13 m)
D. w/o attachment	19'5" (5.91 m)	19'5" (5.91 m)	19'5" (5.91 m)
E. Width of upperstructure	10'0" (3.04 m)	10'0" (3.04 m)	10'0" (3.04 m)
E. Width of upperstructure w/catwalks	11'9" (3.58 m)	11'9" (3.58 m)	11'9" (3.58 m)
F. Track overall length	16'4" (4.98 m)	16'4" (4.98 m)	16'4" (4.98 m)
G. Track overall width w/31.5" (800 mm) shoes	11'2" (3.40 m)	11'2" (3.40 m)	11'2" (3.40 m)
H. Track shoe width	31.5" (800 mm)	31.5" (800 mm)	31.5" (800 mm)
J. Center to center (idler to sprocket)	13'3" (4.04 m)	13'3" (4.04 m)	13'3" (4.04 m)
K. Upperstructure ground clearance	4'0" (1.21 m)	4'0" (1.21 m)	4'0" (1.21 m)
L. Minimum ground clearance	1'7" (0.48 m)	1'7" (0.48 m)	1'7" (0.48 m)
M. Tail swing radius	11'4" (3.45 m)	11'4" (3.45 m)	11'4" (3.45 m)
Working weight*	78,779 lb (35 734 kg)	78,043 lb (35 400 kg)	77,904 lb (35 337 kg)
Ground pressure	7.4 psi (51 kPa)	7.4 psi (51 kPa)	7.4 psi (51 kPa)

*With 31.5" (800 mm) track shoe, 2,544 lb (1154 kg) bucket, 165 lb (75 kg) operator, full fuel and standard equipment.



PERFORMANCE SPECS

	13'3" (4.04 m) Arm	10'8" (3.25 m) Arm	8'8" (2.63 m) Arm
A. Maximum dig radius	39'1" (11.9 m)	36'8" (11.17 m)	35'0" (10.67 m)
B. Dig radius at groundline	38'5" (11.72 m)	36'0" (10.98 m)	34'4" (10.47 m)
C. Maximum dig depth	26'8" (8.14 m)	24'1" (7.34 m)	22'1" (6.73 m)
D. Dig depth - 8'0" (2.44 m) level bottom	26'3" (8.01 m)	23'7" (7.19 m)	21'6" (6.55 m)
E. Dump height	24'9" (7.54 m)	23'9" (7.23 m)	23'5" (7.14 m)
F. Overall reach height	35'0" (10.67 m)	34'0" (10.37 m)	33'10" (10.32 m)
G. Bucket rotation	173°	173°	173°
H. Vertical straight wall dig depth	23'5" (7.15 m)	20'10" (6.35 m)	19'7" (5.97 m)
J. Minimum swing radius	15'0" (4.56 m)	14'9" (4.50 m)	15'2" (4.63 m)
Arm digging force			
Standard	31,586 lb (140.5 kN)	36,846 lb (163.9 kN)	43,838 lb (195.0 kN)
Power Boost	34,306 lb (152.6 kN)	40,016 lb (178.0 kN)	47,435 lb (211.0 kN)
Bucket digging force			
Standard	51,436 lb (228.8 kN)	51,436 lb (228.8 kN)	51,436 lb (228.8 kN)
Power Boost	55,843 lb (248.4 kN)	55,843 lb (248.4 kN)	55,843 lb (248.4 kN)

STANDARD EQUIPMENT

OPERATOR'S COMPARTMENT

Cab with Isomount® system
 Adjustable deluxe seat with
 3" (76 mm) retractable seat belt
 Vandal cover
 Front window safety glass
 Climate Control System
 AM/FM Radio w/ auto tuner
 Roof hatch, skylight
 Sliding Lexan® windows
 Windshield wiper w/washer

ENGINE

Case 6TAA-830 turbocharged
 diesel
 Federal emission certified
 Warm up mode
 Selectable one touch or auto
 accelerator/decelerator

ELECTRICAL

Batteries (2)
 Electronic Systems Monitor
 Horn, dual

HYDRAULICS

ISO pattern pilot controls
 4 Position mode selector:
 H, S, L & Auto
 Auto Power Boost
 2 Variable flow piston pumps
 Auxiliary attachment mode
 Neutral pump destroke
 Auxiliary hydraulic valve
 Boom and arm anti-drift valves
 Selectable cushion control
 for boom and arm
 Controlled free swing
 Ultra Clean filtration system

UNDERCARRIAGE

Shoes: 31.5" (800 mm) 3-bar,
 48 per side
 Track length: 16'4" (4.98 m)
 Track gauge: 8'6" (2.59 m)

TRACK DRIVE

2-speed hydrostatic travel
 Straight tracking travel priority
 Disc-type parking brakes

UPPERSTRUCTURE

Boom: 21'2" (6.45 m) one piece
 Free swing control
 Hammer adaptable, no
 reinforcing required
 Swing brake

OTHER

Counterweight: 16,314 lb (7400 kg)
 Single key vandal lockup

OPTIONAL EQUIPMENT

UPPERSTRUCTURE

Arm: 13'3", 10'8" or 8'8"
 (4.04 m, 3.25 m or 2.63 m)

HYDRAULICS

Auxiliary hydraulics
 Single acting, one pump
 Double acting, single or dual
 pump (includes heavy-duty
 bucket linkage)
 Double acting general purpose
 for use with thumb kit

OTHER

Load holding control devices
 Cylinder mounted
 Case/JRB Slide-Loc® Hydraulic
 Coupler

BUCKETS

Application

Width

SAE Heaped Capacity

General purpose	30" to 60" (0.76 to 1.52 m)	1.26 yd ³ to 2.93 yd ³ (0.96 m ³ to 2.24 m ³)
Heavy-duty.....	30" to 54" (0.76 to 1.37 m)	1.22 yd ³ to 2.53 yd ³ (0.93 m ³ to 1.93 m ³)
Extreme-duty.....	30" to 48" (0.76 to 1.22 m)	1.12 yd ³ to 2.04 yd ³ (0.86 m ³ to 1.56 m ³)
Heavy-duty cast lip.....	39" to 45" (0.76 to 1.14 m)	1.47 yd ³ to 1.76 yd ³ (1.12 m ³ to 1.35 m ³)
Ditching	72" (1.83 m)	2.20 yd ³ (1.68 m ³)

This page intentionally left blank.

NOTE: All specifications are stated in accordance with SAE Standards or Recommended Practices, where applicable.

Form No. CE 336-05-02
Replaces Form No. - CE 336-01-02

IMPORTANT: Case Corporation reserves the right to change these specifications without notice and without incurring any obligation relating to such change. Case Corporation does not warrant the safety or reliability of attachments from other manufacturers.

Visit Case Construction on the Web at:
<http://www.casece.com>
Printed in U.S.A.

© 2002 CASE CORPORATION.
All Rights Reserved.

CX330 Page 6 of 6

**CASE CONSTRUCTION EQUIPMENT
CONTACT INFORMATION**

NORTH AMERICA/MEXICO:
700 STATE STREET
RACINE, WISCONSIN 53404

LATIN AMERICA:
AV. GENERAL DAVID SARNOFF 2237
32210 - 900 CONTAGEM - MG
BELO HORIZONTE BRAZIL

EUROPE/AFRICA/MIDDLE EAST:
18, PLACE DES NYMPHEAS
ZI PARIS NORD 11 95915
ROISSY CDG CEDEX FRANCE

ASIA PACIFIC:
31-67 KURRAJONG ROAD
ST. MARY'S
NEW SOUTH WALES 2760 AUSTRALIA

