

TR3



If you're looking for a three unit trim mower then the Jacobsen TR3 could be just what you need. This machine is perfect for looking after tee boxes and approaches where a high level of quality is required. The full-time all wheel drive and weight transfer control puts power in your hands to handle the toughest terrain.

The main feature of the machine is the ground hugging offset reel configuration with left hand bias that provides an overhang of more than 175 mm (7"), ideal for trimming bunker edges. An ergonomically designed operator platform allows for greater comfort resulting in extended length of use for the operator.



Forward seating position allows exceptional visibility of front units providing added safety to the operator when mowing near bunker edges.

Power: 19.4 kw (26 hp)

Cutting Width: 1.83 m (74")

Drive System: Hydrostatic

Special Features: Ideal for edging tee boxes

Ransomes Jacobsen Ltd

West Road, Ipswich, IP3 9TT UK

Tel: +44 (0) 1473 270000

Web: www.ransomesjacobsen.com



TR3 Technical Data

Power (Diesel)	Engine: Kubota D1105 3 cylinder (in line) Diesel engine 4 stroke, water cooled
	Power: 19.4 kW (26.0 hp) @ 3000 rpm
	Displacement: 1123 cc
	Starting System: 12V electric start
	Fuel Capacity: 45.4 l (10 imp gal)
Drive train	Traction Drive: Full time 3-wheel drive, direct coupled variable displacement pump to direct coupled 200 cc/rev front
	Cutting Unit Drive: Fixed displacement hydraulic motors
Speed	(maximum)
	Cutting: 0 to 9.5 km/h (0 to 5.9 mph)
	Transport: 0 to 14 km/h (0 to 8.7 mph)
	Reverse: 0 to 6 km/h (0 to 3.7 mph)
	Hydraulic Tank Capacity: 25 l (5.49 Imp gal)
	Grade of Hydraulic Oil: Greenscare Biodegradable Oil
Instruments	Lamps: blocked hydraulic filter warning, charge warning, engine coolant temperature warning, engine oil pressure warning, control module fault warning, engine preheat indicator. Multi-function gauge
Controls	Switches: starter key, working light, parking brake, cutter, weight transfer Throttle control lever, joystick unit lift/lower, traction foot pedal, parking brake release valve, transport latches
Brakes	Service: Hydrostatic braking Parking: Electric/Hydraulic parking brake on front wheels
Tyres	Front: 20 x 12.00 - 10 Turf Trac 4pr
	Rear: 20 x 10.00 - 8 Turf Trac 4pr
Steering	Hydrostatic power steering with adjustable tilt steering wheel
Seat	Mechanical suspension. Arm rests. Adjustable weight, height, back rest, head rest and fore - aft
Dimensions	Width of Cut: 1.83 m (72") Transport Width: 2.02 m (79.5")
	Height :1.34 m (52.7") Height with ROPS: 1.85 m (72.8")
	Length: 2.65 m (104.3")
	Weight: 930 kg (2050 lb)
	Ground Pressure: 1 kg/cm ²
	Wheel Track Width : 1.33 m (52.4")
	Wheel Base: 1.5 m (59")
Cutting	Cutting Units: Cylinder
	Weight Transfer Units balanced with hydraulic weight transfer
	Cutting Unit Lift : Joystick control with automatic shut off and safety interlock restart
	Cutting Cylinder: Three 660 mm (26"), 165 mm (6.5") diameter 5-knife fixed head
	Three 660 mm (26"), 165 mm (6.5") diameter 5-knife floating head
	Three 660 mm (26"), 165 mm (6.5") diameter 7-knife floating head
Productivity	Height of Cut: 12 mm to 47 mm (0.47" to 1.85")
	Cutting Productivity: 4.6 mm /km/h (7-knife)
	Clip Rate: 1.62 hectares/hour at 9.5 km/h (3.96 acres/h at 6 mph) 10% allowance is included for normal overlaps and turn at end of each cut
Rollers	Front: Full width 75mm (3") diameter plain or grooved roll
	Rear: Full width 75mm (3") diameter plain roll
Operator Noise	82dB(A)Leq (98/37/EC)
Vibration Levels	1.78 m/s ²
Emissions	Measured sound power: 101 dB(A)LWA
Optional Equipment	Backlap valve kit, work lights, Grammer air suspension seat, grass catchers, rear roller brush kit (factory fitted or field kit)



Tilt adjustable steering

Ransomes Jacobsen Ltd

West Road, Ipswich, IP3 9TT UK

Tel: +44 (0) 1473 270000

Web: www.ransomesjacobsen.com



When Performance Matters®