

GROOM MASTER™ - II

QUICK SPECS

MODELS: Gas or Diesel

DIMENSIONS:

Weight (with rake):
984 lbs. (446 kg)
Length (with rake):
90 in. (2.3 m)
Width (with rake):
73.5 in. (1.9 m)



Combines great ergonomics, power and maneuverability to provide superior productivity.



ERGONOMIC FEATURES

Power steering; Tilt wheel;
Redesigned hydro pedal.

**MORE ATTACHMENTS
- MORE PRODUCTIVITY**

Plow, cultivator, rear rakes,
scarifier with leveling
blade; Ball field conditioner
and box blade available
through RAHN Industries.

**YOUR CHOICE OF POWER
- WITHOUT EXCESS NOISE**

Briggs & Stratton® 18-hp
Vanguard® Twin power gas
engine; 19-hp 3-cylinder
liquid-cooled Kubota®
diesel engine.

STANDARD DRIVE SYSTEM

Series-parallel type
hydrostatic full-time 3-
wheel drive for greater
traction.

REMOTE POWER

12-volt accessory power
outlet, to complete remote
jobs without the hassle.

DEALER INFO:



WHEN PERFORMANCE MATTERS™

©2007 Jacobsen, A Textron Company.
1-888-922-TURF or www.jacobsen.com



MODELS

GROOM MASTER™-II (GAS)	
Engine	Two-cylinder, air-cooled Briggs & Stratton® Vanguard™ V-twin gas
Horsepower	18 hp
Charging System	12-volt, 16-amp alternator; full-size battery
Air Cleaner	Donaldson-type; remote-mounted
GROOM MASTER™-II (DIESEL)	
Engine	Three-cylinder, liquid-cooled Kubota
Horsepower	19 hp
Charging System	12-volt, 40 amp alternator; full-size battery
Air Cleaner	Donaldson-type; remote-mounted

SPECIFICATIONS

PERFORMANCE	
Forward Speed	0 - 9.3 mph (0 - 15 km/h), transport and working
Reverse Speed	0 - 3.5 mph (0 - 5.6 km/h)
Parking Brake	6 in. caliper disc
HYDRAULIC SYSTEM	
Drive	Hydrostatic, three-spool valve for accessories
Hydraulic Oil Capacity	12 qt. (11.4 L), 25-micron filter
Hydraulic System Oil Cooler	Side location; isolation-mounted
Brakes	Hydrostatic braking, with mechanical parking brake
Steering	Automotive-style power steering
Tires	Three 20 x 11.00-10 tubeless, knobby-tread tires
DIMENSIONS	
Length (with rake)	90 in. (2.3 m)
Maximum Width (with rake)	73.5 in. (1.9 m)
Ground Clearance	7.5 in. (19.1 cm)
Wheelbase	40 in. (1 m)
Outside Wheel Tread	59 in. (1.5 m)
Turning Radius	70.5 in. (1.8 m)
Weight (with rake) Three-Wheel Drive	984 lbs. (446 kg)
Fuel Capacity	4.5 gal. (17.1 L)

ACCESSORIES

FACTORY INSTALLED:	
<input type="checkbox"/>	Crating (stackable)
DEALER INSTALLED:	
<input type="checkbox"/>	Blade, Manual Lift
<input type="checkbox"/>	Cultivator (Includes Hydraulic Controls)
<input type="checkbox"/>	Drag Mat with Carrier
<input type="checkbox"/>	Fan Rake, Add-On or Stand-Alone
<input type="checkbox"/>	Hydraulic Controls for Blade or Scarifier (Must be used with Manual Lift Blade to Convert Manual Blade to Hydraulic Control)
<input type="checkbox"/>	Rear Rake Implement
<input type="checkbox"/>	Scarifier with Leveling Blade (Does Not Include Hydraulic Lift Controls)
<input type="checkbox"/>	Infield Conditioner, Box Blade (Through RAHN Industries)

NOTE: Specifications, while correct at time of printing, may change without notice. This product has been tested and complies with B71.4 -2004 ANSI voluntary safety specifications for commercial turf equipment and also complies with EU safety regulations.