

# JACOBSEN® TR-3™

## QUICK SPECS

MODELS: Diesel

CUTTING REELS:

7-Blade Reels  
26 in. (660 mm)

HEIGHT OF CUT:

0.37 - 2.75 in.  
(9.5 - 69.8 mm)

WIDTH OF CUT:

72 in. (1.83 m)

DIMENSIONS:

Weight: 2,050 lbs. (930 kg)  
Length: 104.3 in. (2.65 m)  
Height: 52.7 in. (1.34 m)  
Width: 79.5 in. (2.02 m)



On-demand traction control puts power in your hands to handle rough terrain.



### THREE-WHEEL DRIVE

Parallel-series traction system maintains traction to two wheels preventing slippage on all areas of your course.

### OIL-IMMERSED ZERO MAINTENANCE PARKING BRAKES

Reliable brakes delivering safe braking on even the steepest slopes.

### 26-HP KUBOTA® DIESEL ENGINE

Power to handle the most difficult cutting conditions. It provides smooth acceleration and is quiet to operate.

### PROVEN TRI-KING® REELS

Heavy-duty 26" wide reels deliver exceptional quality of cut year after year.

### UNIQUE ALL-OUT-FRONT DESIGN

The driver has an unobstructed view of the cutting path. Plus, you don't have to sit on a hot engine all day long.

DEALER INFO:



WHEN PERFORMANCE MATTERS™

©2007 Jacobsen, A Textron Company.  
1-888-922-TURF or [www.jacobsen.com](http://www.jacobsen.com)



MODELS

<b>TR-3™</b>	
Engine	3-cylinder, liquid-cooled Kubota diesel
Horsepower	26 hp (19.4 kW)
Displacement	68.55 cu. in. (1,123 cc)
Oil Capacity	1.35 gal. (5.1 L)
Air Cleaner	Donaldson dry cartridge type
Lubrication	Full flow oil filter with replaceable spin-off type filter
Electrical System	12V starter; 40 amp alternator/regulator

Grooved front (steel)	26 in. (660 mm)
Solid	26 in. (660 mm)
Height of Cut	0.37 - 2.75 in. (9.5 - 69.8 mm)
Cutting Capacity	2.6 acres/hr. at 5.9 mph (1.0 ha/h at 9.5 km/h)
Overall Cutting Width	72 in. (1.83 m)
Cutting Frequency	0.151 in./mph (3.8 mm/kph)

SPECIFICATIONS

<b>VEHICLE</b>	
Traction Drive	Parallel series three wheel drive with direct-couple hydrostatic with high-torque wheel motors
Reel Drive	Fixed-displacement, three-section gear pump and three bi-directional gear motors connected in parallel
Steering	Hydrostatic power; rear wheel
Fuel	Capacity 12 gal. (45.4 L)
<b>TIRES</b>	
Front	20 X 12- 10 Turf Trac 4 ply
Rear	20 X 10 - 8 Turf Trac 4 ply
<b>BRAKES</b>	
Service	Dynamic braking through hydrostatic drive
Parking	Hydraulic wet disc brakes on front wheel
Instruments	Engine coolant temperature, voltmeter, hour meter, engine low oil warning light, control module warning light, engine preheat indicator light, hydraulic filter indicator light
Controls	Foot operated traction pedal, hand throttle, ignition switch, headlight switch, parking brake switch, reel control switch, weight transfer switch, joystick lift/lower
Seat	High-back, front-to-rear adjustment
<b>SPEED</b>	
Transport	0-8.5 mph (0-14 km/h); Mowing 0-6 mph (0-9.5 km/h)
Reverse	0-3.7 mph (0-6 km/h)
<b>DIMENSIONS</b>	
Overall Length	104.3 in. (2.65 m)
Overall Height (without O.P.S.)	52.7 in. (1.34 m)
Overall Width - Mow and Transport	79.5 in. (2.02 m)
Weight	2,050 lbs. (930 kg)

ACCESSORIES

<input type="checkbox"/>	LH front 26" x 7-blade reel
<input type="checkbox"/>	RH front 26" x 7-blade reel
<input type="checkbox"/>	Center 26" x 7-blade reel
<input type="checkbox"/>	Fixed OPS
<input type="checkbox"/>	26" Grooved steel front rollers (Set of 3)
<input type="checkbox"/>	26" Grooved front roller scrapers (Set of 3)
<input type="checkbox"/>	(1) 26" Rear roller scraper (3 required)
<input type="checkbox"/>	26" Grass catchers, gray w/hardware (Set of 3)
<input type="checkbox"/>	Back lap valve kit
<input type="checkbox"/>	Working Lights

NOTE: Specifications, while correct at time of printing, may change without notice. This product has been tested and complies with B71.4 -2004 ANSI voluntary safety specifications for commercial turf equipment and also complies with EU safety regulations.

REELS

Number and Size	3 - 26 in. (0.66 m), 7 in. (187 mm) diameter
Reel	7 blade reel - 26 in. (660 mm)
Number of Blades	7
Blade Material	Hardened, high-manganese carbon steel
Reel Diameter	7 in (17.8 cm)
<b>ROLLERS</b>	
Grooved front (nylon)	26 in. (660 mm)