



## G - STAR BUNKER RAKE SPECIFICATION

---

<b>POWER</b>	16hp (12 kW) Vanguard V twin cylinder , air cooled, gasoline Cast iron sleeves, 29.3 cu.In. displacement, electronic ignition, Full pressure lubrication with oil filter Engine mounted air cleaner and remote mounted 3 phase Donaldson air intake filtration
<b>CONFIGURATION</b>	3-wheel tricycle configuration, 9" (23 cm) ground clearance
<b>DRIVE</b>	Torque converter drive from engine to Geared transaxle
<b>SPEED</b>	Infinately variable (by engine speed), 0-12 mph (0-20 kph)
<b>BRAKING</b>	Disc braking on transaxle. Foot pedal actuated. Locking park brake
<b>MAIN FRAME</b>	Heavy gauge square steel tubing, hydraulically formed, electrically welded. Rear engine placement.
<b>TIRES/WHEELS</b>	Purchasers choice of (3) 22-1100 x 8 knobbed sand tires, -or- (3) 22-1100 x 8 turf tires
<b>STEERING</b>	Manual front wheel steering, 15 in (38 cm) diameter automotive type steering wheel, adjustable tilt
<b>CONTROLS</b>	Foot pedal accelerator, foot pedal brake Electric actuator for rear implement lift/lower (Optional) manual control for center mounted implements
<b>SEAT</b>	Deluxe seat, padded, vinyl covered, 1 piece molded, _ back support
<b>ELECTRICAL</b>	12 volt battery (280 cca); 12 volt electric starter, side mounted Ignition switch, operator presence switch in seat.
<b>SOUND LEVEL</b>	82dB(A) under normal operating conditions
<b>DIMENSIONS (Inches/cm)</b> (Length-Width-Height)	56 in (142cm)-74 in (188 cm)-46 in (116cm); Wheelbase: 40 in (101cm)
<b>WEIGHT</b>	650 lbs (295 kg)
<b>LIQUID CAPACITIES</b>	Hydraulic system oil: 5 gallons (19 liter) in high density polyethylene tank Gasoline (unleaded): 5 gallons (19 liter) in high density polyethylene tank
<b>SAFETY &amp; CONFORMANCE</b>	Complies with all applicable ANSI, OSHA, and European Machinery Directive standards

## IMPLEMENTS

Many efficient and effective implements for constructing and maintaining sand bunkers and other areas on the golf course. Please see chart below.

### Rear Mounted Implements

		<b>WEIGHT</b>
<b>13-298</b>	Fan Rake for Sand Traps	36
<b>13-319</b>	Fan Rake Add On for 13-438 Rake Assembly	20
<b>13-438</b>	Sand Trap Rake Assembly	66
<b>13-684</b>	Brush Attachment for all rakes except 42-130, 42-026	20
<b>42-128</b>	72" (189 cm) Stainless Steel Tournament Rake	75
<b>42-132</b>	72" (189 cm) Mild Steel Tournament Rake	75

### Center Mounted Implements

<b>42-008</b>	Sand Cultivator	20
<b>42-340</b>	Sand Cultivator w/ spring tine teeth	20
<b>42-401</b>	Manual Lift for Center Implements	20

### Front Mounted Implements

<b>42-011</b>	Front Mounted Plow (aluminum blade)	65
---------------	-------------------------------------	----