

WideSpin™ 1530

Tow-Behind Broadcast Topdresser
No Engine / Hydraulically Driven



The WideSpin 1530 Tow-Behind with no engine is an economical option for any course. It uses the hydraulics of your vehicle to drive the spinners.

- Topdresses so light that it requires no dragging.
- 30 ft wide light application allows you to topdress 18 greens in 90 minutes.
- Switch from light spread to 15 ft heavy spread for after aerification in five minutes.
- Spinner angle is adjustable from 0-15° for greater control and better penetration of turf, even on windy days.
- Galvanized hopper for worry-free, rust proof durability—no paint to get sanded away.
- Three-position control operates belt and spinner independently.



Adjustable twin spinners angle down for better penetration of turf.



Three-position control operates belt and spinner independently.

Accessories



Trench Filler Attachment

A trench filler attachment gives the WideSpin 1530 even more uses—and saves time and labor. Prod. No. 86150



Cross-Conveyor Attachment

Expand your 1530's usefulness by allowing it to be used for material handling duties. Quickly and easily attach without tools. Use to top off bunkers, add mulch to flowerbeds, level and repack sprinkler heads and more. Prod. No. 86172

Specifications	
Model:	WideSpin™ 1530 Tow-Behind No Engine / Hydraulically Driven; Cushman® product number 85814; John Deere® and Toro® product number 85815.
Hopper Capacity:	19 cubic feet or 1,800 pounds (0.54 cubic meter or 816.5 kg), galvanized panels
Transport Speed:	5 MPH (8 km/h)
Hopper Size:	74" x 32" (1.88 x 0.81 meter) at top
Spreading Width:	15' to 30' (9.14 meters)
Topdressing Speed:	Up to 8 MPH (12.8 km/h)
Spread Application:	From as little as 1/32" (0.08mm) to more than 1/4" (6.35mm) using patented WideSpin Technology.
Operating Ground Speed:	5 MPH (8 km/h)
Metering Gate:	Full manual adjustment for LIGHTSPREAD™ and HEAVYSPREAD™ operation.
Controls:	Patented three-position control operates belt and spinners independently.
Electrical Requirements:	12 Volt DC, negative ground, 15 AMP Supplied by truck.
Minimum Hydraulics Requirements:	7 GPM at 1,500 PSI (27 liters per minute at 10,400 kPa)
Hydraulic Power and Fluid:	Supplied by truck.
Empty Weight:	1,019 lbs (462 kg)
Weight Loaded:	2,819 lbs (1,279 kg)
Optional:	Trench-filler attachment, product number 86150; 5th wheel hitch, product number 86138 Cross Conveyor attachment, product number 86172.

WIDESPIN is a trademark of Turfco Manufacturing, Inc.
Cushman is a registered trademark of Cushman Textron
John Deere is a registered trademark of John Deere Co., Inc.
Toro is a registered trademark of The Toro Co.

Specifications subject to change without notice.