

# WideSpin 1530

Truck-Mounted Broadcast Topdresser



Turn your turf truck into a quality broadcast topdresser with the WideSpin 1530 Truck-Mounted model. A few simple mounting brackets and connections attach this custom-fit topdresser to your four-wheel Cushman® Turf-Truckster®, John Deere ProGator™ or Toro® Workman®. Units are designed for turf vehicles and their weight capacity, so that weight levels aren't exceeded.

- Topdresses so light that it requires no dragging.
- 30 ft wide light application allows you to topdress 18 greens in 90 minutes.
- Switch from light spread to 15 ft heavy spread for after aerification in five minutes.
- Spinner angle is adjustable from 0-15° for greater control and better penetration of turf, even on windy days.
- Galvanized hopper for worry-free, rust proofdurability—no paint to get sanded away.
- Patented three-position switch guarantees spinners turn on before conveyor ensuring a clean application every time.
- Trench filler attachment available.
- Cubic feet hopper minimizes weight on greens and turf truck.



*John Deere ProGator*



*Toro Workman*

## Specifications

Model:	WideSpin™ 1530 Truck-Mounted; Cushman number 85811 (includes mounting kit); John Deere number 85813, requires mounting kit number 86161; Toro number 85813, requires mounting kit number 86160.
Hopper Capacity:	19 cubic feet (0.54 cubic meters), galvanized panels.
Hopper Size:	Cushman model is 60" x 37" inches (1.52 x 0.94 meter) at top; John Deere and Toro models are 74" x 32" (1.88 x 0.81 meter) at top
Spreading Width:	15' to 30' (9.14 meters)
Spread Application:	From as little as 1/32" (0.08mm) to more than 1/4" (6.35mm) using patented WideSpin Technology.
Conveyor Belt:	18" (0.46 meter) wide, pebble surface composition with heavy-duty polyester cord.
Metering Gate:	Full manual adjustment for LIGHTSPREAD™ and HEAVYSPREAD™ operation.
Operator Controls:	Patented three-position control operates belt and spinners independently.
Drive:	Trucks hydraulic system powers the belt and spinner plates.
Empty Weight:	660 lbs. (299 kg)—85811 629 lbs. (285 kg)—85183
Turf Truck Requirements:	Cushman: Hi-lo hydraulic accessory must be installed on truck (part number 894712 for gas or 894713 for diesel). John Deere: Hydraulic auxiliary kit required; comes standard on vehicle. Toro: Hi-lo hydraulic accessory must be installed on truck (part number 07228).
Optional:	Trench-filler attachment, product number 86150; cross conveyor attachment, product number 86172; storage stand, product number 86139.

WIDESPIN is a trademark of Turfco Manufacturing, Inc.  
TURFCO is a registered trademark of Turfco Manufacturing Inc.  
Cushman is a registered trademark of Cushman Textron  
Turf-Truckster is a registered trademark of Cushman Textron  
ProGator is a registered trademark of John Deere Co., Inc.  
Workman is a registered trademark of The Toro Co.